





Kwalu Features


Product Dimensions and Specs

Overall	54W 33.5D 37.5H
Seat	49W 20D 19H
Arm	26H
Wt.	92 lbs
Wt. Capacity	500 lbs


Product Configurations

Arezzo Collection	AREXX	
Chair Style	 <b>L</b> Lounge	
Seat Style	 <b>1</b> Chair	 <b>2</b> Love Seat
Piping Style (Optional)	 <b>P</b> With Piping	


Product Statement of Line Images




Arezzo Lounge Chair, Back &  
Seat Cushions without Piping  
Model: AREL1  
28W 33.5D 37.5H  
26AH



Arezzo Lounge Chair, Back &  
Seat Cushions with Piping  
Model: AREL1P  
28W 33.5D 37.5H  
26AH



Arezzo Love Seat, Back &  
Seat Cushions without Piping  
Model: AREL2  
54W 33.5D 37.5H  
26AH



Arezzo Love Seat, Back &  
Seat Cushions with Piping  
Model: AREL2P  
54W 33.5D 37.5H  
26AH

## Product Features



Waterproof Outdoor UV Protected Frame

Special additive protects frame against the elements and damaging ultraviolet rays.



Steel Reinforced

Our patented steel-reinforced joint system uses over 20 pieces of steel in most Kwalu chairs. Stop ongoing and costly furniture replacement.

[Learn More >](#)



Quick Dry Cushion

Kwalu's quick drying cushion construction moves moisture through fast allowing cushions and pillows to dry rapidly.



Optional Piping on Back Pillow and Seat

Piping available on back pillows and seat cushions and is optional.



Number of Seats

Choose from 2 seat styles - lounge chair and love seat.

[Learn more >](#)



Replacement Cushions

Please contact a sales associate to purchase additional or replacement cushions.



Optional Floor Mounting


A set of 4 L-shaped brackets and 8 screws to secure the brackets to the product are provided. Screws to attach brackets to the floor are not included.

## Product Glides


Nylon Knock in Glide 1 1/8 inch

## Product Finishes

### Frame Finish



Outdoor  
Weathered Teak  
UV



Outdoor White  
UV

## Product Environmental Certifications

